




134

150.1010

EAN 4042146825877

- Ø 1 mm
- 40%
- Ø 0,6 mm 0,8 mm
- 100 - 200°C
- 5

- 3-4
- W:** 30 Watt
-
-
-
- 1
- mm:** 140
- mm:** 270
- mm:** 48
-
- 90 min
- 5
- 0°C +500°C
- Stoßstangen, Abdeckungen, Verkleidungen, etc.
- (V):** 3,7
-
- Micro USB - USB-A
- 134
- g:** 539
-
- 1



□□

□□□	□□		□□	□□□□□□ □□□□□□□□
150.1011	1 x		□□□□□□□□□□30 □	□□□□□□□□□□
150.1012	1 x		□□□□□1 m USB □□□ Micro-USB □□	□□□□□□□□□□
150.1013	1 x		□□□□□□	□□□□□□□□□□
150.1014	1 x		□□□□□□□	□□□□□□□□□□
150.1016	1 x		□□□□□□□□□□	□□□□□□□□□□
150.1017	1 x		□□□□□□□□□□□□	□□□□□□□□□□
150.1018	1 x		□□□□□□□□□□□□□□	□□□□□□□□□□
150.1062	1 x		□□□ U □□□□□□□□ 0.6 mm□50 □	□□□□□□□□□□
150.1063	1 x		□□□ U □□□□□□□□ 0.8 mm□50 □	□□□□□□□□□□
960.1121	1 x		□□□□□, 3 □□, 100x55mm	□□□□□□□□□□
960.1122	1 x		PE□□□□□□□□□□□□, 6 □□, □□	□□□□□□□□□□
960.1123	1 x		PP□□□□□□□□□□□□, 6 □□, □□	□□□□□□□□□□
960.1124	1 x		PS□□□□□□□□□□□□, 6 □□, □□	□□□□□□□□□□
960.1125	1 x		ABS□□□□□□□□□□□□□□□□□□, 6 □□, □□	□□□□□□□□□□